



DRUM STAND

For safe and effective rollout of cable

Safe cable rollout

A drum safely attached to a drum stand creates better fiber blowing results as it protects the cable. With this cable drum's ball bearings you get near frictionless rotation.

Easy crank mechanism

The drum stand is equipped with a hand operated mechanical lifting system of five (5) lifting arms 100 mm apart making it easy to lift the drum.

Detachable frame type

Complete drum carrying steel shaft with one pair of drum centering cones. The frame can be folded for easy transportation.

Made of galvanized steel

Holds drums up to 3,500 lbs in weight and up to 70" in diameter.

COMPATIBLE WITH

MiniFlow RAPID (Item No.: 101-190108010)
 • For microfiber and cable 3-12 mm

PowerFlow RAPID (Item No.: 101-41001)
 • For cable 5.5-25 mm

MultiFlow RAPID (Item No.: 101-41002)
 • For cable 5.5-32 mm

SPECIFICATIONS

Item No.:	101-20011
Drum diameter:	Up to 1800 mm (70.8")
Max. weight of drum:	1600 kg (3527 lbs)
Max. width of drum:	1200 mm (47.2")
Physical size of shaft:	1400 mm (55")
Weight:	28.5 kg (62.8 lbs)
Length:	750 mm (29.5")
Width:	560 mm (22")
Height:	420 mm (16.5")

