



DUCTROD RAPID

Designed to push a duct rod into an underground duct.

Tool free installation

When utilizing DuctRod RAPID, the configuration and installation can be deployed without any usage of tools. This makes every job more effective as the machine can quickly be adapted to the specific job saving you time.

Adaptable to various manholes

It is equipped with a flexible clamping unit, allowing you to attach the machine to the sidewall of the manhole securing more stable installation.

Effective rod pushing

Each job is mechanized, which help you improve efficiency and minimizes the risk of costly errors. For rods up to 25 mm.

Adjustable Torque Distance and Speed measurement for complete rod control

SPECIFICATIONS

Item No.:	101-230320001
Rod diameter:	9-25 mm (.35-.98")
Duct diameter:	10-40 mm (.39-1½")
Installation speed:	Up to 80 m/min (262 ft)
Max. hydraulic pressure:	110 bar (1,595 psi)
Pushing/pulling force:	0-200 kg (0-440.9 lbs)
Clamping unit range:	475-900 mm (18.7"-35.4")
Weight:	68 kg (150 lbs)
Length ¹⁾ :	1050 mm (41")
Width:	475 mm (18.7")
Height:	790 mm (31.1")

¹⁾ Without clamping unit

DON'T FORGET TO ORDER

Hydraulic Power Pack

Item No.: 101-10102

Extension hoses

- 5 m/16ft extension hose set.
Item no.: 103-130208001
- 15 m/49ft extension hose set.
Item no.: 103-20258

INCLUDED

When purchasing DuctRod RAPID

- 1¼" duct clamp set (outlet) & ¾" duct clamp set (inlet)
- 1 set of chains (8-16 mm)
- Control valve for DuctRod RAPID

